

Safety Data Sheet

## Mineral Oil

Sheet | White Mineral Oil, Petroleum Hydrocarbon

Olathe, KS Tel: 913-390-6184

1. Product Identity

Emergency phone: 800 424 9300 (Chemtrec)

NFPA Rating: Health 0, Flammability 1, Reactivity 0 Special 0 HMIS Rating: Health 0 Flammability 1, Physical 0, Reactivity, 0

Product Name: Mineral Oil

Product Number: 44

2. Hazardous Ingredients

White Mineral Oil

**Aspiration Toxicity** 



Signal Word: Danger

Hazard Statement: May be fatal if swallowed & enters

airways

**Precautionary Statements:** Take time observe label directions. If taken internally, do not induce vomiting. Keep away from heat & open flame. Keep container closed when

not in use. Store at 15°-30°C (59°-86°F). Wash skin

thoroughly after handling.

3.Composition

White Mineral Oil

Weight%: White Mineral Oil: CAS: 8042-47-5: 100%

Vitamin E: CAS: 10191-41-0: Less than 20ppm

#### 4. First Aid Measures

Eye Contact: If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.

Skin Contact: Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

Inhalation (Breathing): First aid is not normally required. If breathing difficulties develop, move away from source and seek medical attention.

Ingestion (Swallowing): First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

Most Important symptoms/effects, acute and delayed:

EYES: May cause slight irritation, tears and a burning sensation

SKIN: Causes mild irritation, potentially causing reddening, itching or inflammation

INHALATION: Respiratory tract irritation may occur if exposed to fumes or mists

INGESTION: Symptoms may include nausea, vomiting and diarrhea Aspiration into lungs may cause chemical pneumonia and lung damage. Medical Attention and Special Treatment needed: Treat symptomatically

INGESTION: If ingested, this material represents a significant aspiration and chemical pneumonitis hazard. Vomiting is not recommended.

### 5. Fire Fighting Measures

<u>Suitable Extinguishing Media:</u> Dry chemicals, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

<u>Unsuitable Extinguishing Media:</u> Avoid solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture: Elevated temperatures can lead to the formation of irritating fumes and vapors.

Decomposing products may include the following materials: Carbon Dioxide and Carbon Monoxide. Product is a static accumulating liquid. Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire. Static Electricity accumulation may be increased by the presence of small quantities of water or other contaminates. Restrict flow velocity to avoid build-up of static charge.

Advice for firefighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant. Isolate immediate hazard area, keep unauthorized personnel out. Water spray may be useful minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done with minimal risk.

### 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment to avoid direct contact. The material will burn, but will not ignite readily. Keep all ignition sources away from the spill/release.

<u>Environmental Precautions:</u> Stop spill/release if it can be done safely. Product is insoluble in water, so prevent it from entering drains or water ways. Notify appropriate state and local authorities.

Method for clean up: Use absorbent materials such as sand, earth or vermiculite on land spills. Use absorbent booms or skimming devices on water spills.

#### 7. Handling & Storage

<u>Handling:</u> Keep away from ignition sources. Be cautious of any drips or spills as product is extremely slippery. Do not enter confined spaces without appropriate equipment and procedures. Electrostatic charge may accumulate and create a hazardous condition when handling this material. Bond and Ground lines and equipment used during transfer to reduce the possibility of static spark-initiated fire.

<u>Storage:</u> Store containers in a clean, dry location, away from strong sunlight and heat or flames. Keep containers sealed when not in use. Empty containers retain residue and should be handled with care and disposed of properly.

#### 8. Control Measures

OSHA: 5 mg/m ACGIH TWA: 5 mg/m ACGIH STEL: 10mg/m Appropriate Engineering Controls: Consider the following when employing engineering controls and selecting personal protective equipment: Potential hazards of the material, applicable exposure limits, job activities and other substances in the work place. If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

Personal Protective Equipment (PPE):

Respiratory: If vapor or mist is generated by heating, spraying, etc, wear an air purifying respirator with mist filter. No special respiratory protection is normally required. Skin: Wear gloves and long sleeve clothing to minimize contact.

Eye/Face: Wear glasses with side shield or goggles in case of splashing

#### 9. Physical Properties

Appearance: Liquid, Water White

Odor: None pH: N/A

Melting/Freezing Point: < 10°F

Initial Boiling Point: (SEE PRODUCT BULLETINS FOR

SPECIFICS)

Flash Point: >350°F / 177°C (SEE PRODUCT BULLETINS

FOR SPECIFICS)

Test Method: Cleveland Open Cup (COC), ASTM D92

Evaporation Rate: Not Applicable

Flammability (solid, gas) Not Applicable LEL (vol % in air): No

data UEL (vol % in air): No data

Vapor Pressure: 1

Specific Gravity: 0.82 – 0.88 (SEE PRODUCT BULLETINS

FOR SPECIFICS)

Solubility in Water: Insoluble Partition coefficient: log POW:

>6 This product is soluble in oil
Auto-ignition Temperature: No data
Decomposition Temperature: No data

Viscosity: 50 – 130 SUS @100°F (SEE PRODUCT

**BULLETINS FOR SPECIFICS)** 

Note: Unless otherwise stated, values are determined at

20°C (68°F) and 760 mm Hg (1 atm)

# 10. Stability & Reactivity

Reactivity: Not chemically reactive

Chemical Stability: Stable under normal ambient and

anticipated conditions of use

Possibility of hazardous reactions: Not anticipated under

normal conditions

Conditions to Avoid: Extended exposure to high temperatures can cause decomposition.

Materials to Avoid (Incompatible Materials): Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Not anticipated under

normal conditions

## 11. Toxicological Information

Acute Health Effects

Inhalation: May be fatal if enters

airways

Ingestion: Call Poison Control
Skin Contact: Unlikely to be harmful

#### Chronic Health Effects:

Aspiration Hazard: inhalation of mist or spray may be harmful and cause pulmonary edema or aspiration pneumonia. Oil deposits in the lungs may lead to fibrosis and reduced pulmonary function.

Skin: may cause mild irritation

Eye: causes mild irritation

### 12. Ecological Information

No additional information is available at this time.

### 13. Disposal Information

#### Waste disposal method:

This product is not hazardous as supplied. Please refer to local waste disposal regulations for further information. Empty drums/containers should be sealed and returned to a reconditioner.

# 14. Transport Information

DOT Class: Not a DOT Controlled material

Hazard Class: N/A
UN Number: N/A
Package code: N/A

Shipping Name: Not regulated.

#### 15. Regulatory Please refer to local waste disposal regulations for further Information information. 16. Other Information Disclaimer of Expressed and implied Warranties: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE. OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license Date Created: 07/23/2014